

# SAFETY DATA SHEET

DOW CHEMICAL COMPANY LIMITED

Safety Data Sheet according to Reg. (EU) No 2015/830

Product name: BETACLEAN ™ 3300

Revision Date: 05.01.2018 Version: 15.0 Date of last issue: 08.03.2017 Print Date: 06.01.2018

DOW CHEMICAL COMPANY LIMITED encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier Product name:** BETACLEAN ™ 3300

**1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses:** Cleaner. For use in automotive applications.

1.3 Details of the supplier of the safety data sheet COMPANY IDENTIFICATION DOW CHEMICAL COMPANY LIMITED STATION ROAD, BIRCH VALE, HIGH PEAK DERBYSHIRE England SK22 1BR UNITED KINGDOM

**Customer Information Number:** 

+44 (0) 203 139 4000 SDSQuestion@dow.com

**1.4 EMERGENCY TELEPHONE NUMBER 24-Hour Emergency Contact:** 0031 115 694 982 **Local Emergency Contact:** 00 31 115 69 4982

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008:

Eye irritation - Category 2 - H319 For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008:

#### Hazard pictograms



#### Signal word: WARNING

#### Hazard statements

H319 Causes serious eye irritation.

#### **Precautionary statements**

P264	Wash skin thoroughly after handling.
P280	Wear eye protection/ face protection.
P305 + P351	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,
+ P338	if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.

#### 2.3 Other hazards

No data available

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2 Mixtures

This product is a mixture.

CASRN / EC-No. / Index-No.	REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008
CASRN 67-63-0 EC-No. 200-661-7 Index-No. 603-117-00-0	01-2119457558-25	> 5.0 - < 15.0 %	Isopropanol	Flam. Liq 2 - H225 Eye Irrit 2 - H319 STOT SE - 3 - H336
CASRN 111-76-2 EC-No. 203-905-0 Index-No. 603-014-00-0	01-2119475108-36	> 1.0 - < 5.0 %	2-butoxyethanol	Acute Tox 4 - H302 Acute Tox 4 - H332 Acute Tox 4 - H312 Skin Irrit 2 - H315 Eye Irrit 2 - H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

### **SECTION 4: FIRST AID MEASURES**

# 4.1 Description of first aid measures General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Wash off with plenty of water.

**Eye contact:** Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

**Ingestion:** Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

**4.2 Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

#### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician:** Maintain adequate ventilation and oxygenation of the patient. Hemodialysis may be of benefit if substantial amounts have been ingested and the patient is showing signs of intoxication. Consider hemodialysis for patients with persistent hypotension or coma unresponsive to standard therapy (isopropanol levels >400 - 500 mg/dl). (Goldfrank, Toxicological Emergencies 7th ed., 2002; King, JAMA, 1970, 211:1855). No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis. Repeated excessive exposure may aggravate preexisting blood disease (anemia).

# **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

**Suitable extinguishing media:** This material does not burn. If exposed to fire from another source, use suitable extinguishing agent for that fire.

Unsuitable extinguishing media: No data available

5.2 Special hazards arising from the substance or mixture Hazardous combustion products: Not applicable

Unusual Fire and Explosion Hazards: No data available

#### 5.3 Advice for firefighters

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. This material does not burn. Fight fire for other material that is burning.

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:** Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

**6.2 Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

**6.3 Methods and materials for containment and cleaning up:** Non-combustible material. Contain spilled material if possible. Absorb with materials such as: Cat litter. Sand. Sawdust. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

**6.4 Reference to other sections:** References to other sections, if applicable, have been provided in the previous sub-sections.

# SECTION 7: HANDLING AND STORAGE

**7.1 Precautions for safe handling:** Keep away from heat, sparks and flame. No smoking, open flames or sources of ignition in handling and storage area. Electrically ground and bond all equipment. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

**7.2 Conditions for safe storage, including any incompatibilities:** Store in accordance with good manufacturing practices.

Storage stability Storage temperature: > 5 - < 25 °C

7.3 Specific end use(s): See the technical data sheet on this product for further information.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

R			-	Value	Notation
				2	200 ppm
	ACGIH	ł	STEL	4	00 ppm
	GB EH40	)	TWA	999 mg/m3 4	00 ppm
			STEL	1,250 mg/m3 5	500 ppm
	ACGIH	ł	TWA		20 ppm
	2000/39/EC	;	TWA	98 mg/m3	20 ppm
	2000/39/EC	;	TWA		SKIN
			STEL	246 mg/m3	50 ppm
	2000/39/EC	;	STEL		SKIN
	GB EH40	)	TWA		SKIN
	GB EH40	)	STEL		SKIN
			TWA		25 ppm
		)	STEL		50 ppm
		•	-		
CAS-No.	Control	-			Basis
	parameters			concentration	
37-63-0	Acetone	Urine		40 mg/l	ACGIH
					BEI
			workweek		
11-76-2					
	•	Urine	After shift		GB EH40
	c acid			•	BAT
	•	Urine			ACGIH
			•	Creatinine	BEI
	(BAA)		soon as		
			•		
			after		
			exposure		
			ceases)		
Acute loca	laffaata	Long-term s	votomio	Long-term local	affa ata
		ACGIH GB EH40 GB EH40 ACGIH 2000/39/EC 2000/39/EC 2000/39/EC 2000/39/EC GB EH40 GB EH4	ACGIH ACGIH GB EH40 GB EH40 ACGIH 2000/39/EC 2000/39/EC 2000/39/EC 2000/39/EC 2000/39/EC 2000/39/EC GB EH40 GB EH40 GB EH40 GB EH40 GB EH40 GB EH40 Specimen 37-63-0 Acetone Urine c acid Butoxyaceti Urine c acid	ACGIH TWA ACGIH STEL GB EH40 TWA GB EH40 STEL ACGIH TWA 2000/39/EC TWA 2000/39/EC STEL 2000/39/EC STEL 2000/39/EC STEL GB EH40 STEL STE STEL GB EH40 STEL GB EH40 STEL STE STE STE STE STE STE STE STE STE STE STE STE STE STE STE	ACGIH TWA 2 ACGIH STEL 4 GB EH40 TWA 999 mg/m3 4 GB EH40 STEL 1,250 mg/m3 5 ACGIH TWA 2000/39/EC TWA 98 mg/m3 2000/39/EC STEL 246 mg/m3 2000/39/EC STEL 246 mg/m3 2000/39/EC STEL 246 mg/m3 2000/39/EC STEL C GB EH40 TWA GB EH40 STEL GB EH40 STEL STE STE STE STE STE STE STE STE STE STE

Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	888 mg/kg	500	n.a.	n.a.
				bw/day	mg/m3		

#### Consumers

Acute	Acute systemic effects Acute local effects		Long-te	rm systemi	c effects	•	erm local ects		
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	319 mg/kg	89 mg/m3	26 mg/kg bw/day	n.a.	n.a.
					bw/day	mg/ms	Dw/uay		

# 2-butoxyethanol Workers

Acute syste	emic effects	Acute local effects		Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
125 mg/kg	1091	n.a.	246	125 mg/kg	98 mg/m3	n.a.	n.a.
bw/day	mg/m3		mg/m3	bw/day			

#### Consumers

Acute systemic effects		Acute systemic effects Acute local effects		Long-term systemic effects			-	erm local ects	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
89 mg/kg	426	26.7	n.a.	147	75 mg/kg	59	6.3	n.a.	n.a.
bw/day	mg/m3	mg/kg		mg/m3	bw/day	mg/m3	mg/kg		
		bw/day					bw/day		

### **Predicted No Effect Concentration**

Isopropanol

Compartment	PNEC
Fresh water	140.9 mg/l
Marine water	140.9 mg/l
Intermittent use/release	140.9 mg/l
Fresh water sediment	552 mg/kg dry weight (d.w.)
Marine sediment	552 mg/kg dry weight (d.w.)
Sewage treatment plant	2251 mg/l
Soil	28 mg/kg dry weight (d.w.)
Oral	160 mg/kg

#### 2-butoxyethanol

Compartment	PNEC
Fresh water	8.8 mg/l
Intermittent use/release	9.1 mg/l
Marine water	0.88 mg/l
Sewage treatment plant	463 mg/l
Fresh water sediment	34.6 mg/kg dry weight (d.w.)

Marine sediment	3.46 mg/kg dry weight (d.w.)
Soil	2.33 mg/kg dry weight (d.w.)
Oral	20 mg/kg

#### 8.2 Exposure controls

**Engineering controls:** Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

#### Individual protection measures

**Eye/face protection:** Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent. If exposure causes eye discomfort, use a full-face respirator. **Skin protection** 

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Polyethylene. Neoprene. Chlorinated polyethylene. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Avoid gloves made of: Polyvinyl alcohol ("PVA"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

Use the following CE approved air-purifying respirator: Organic vapor cartridge, type A (boiling point >65 °C)

#### **Environmental exposure controls**

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1 Information on basic physical and chemical properties Appearance

Liquid.
Blue
Alcohol
No test data available
8.5 Calculated.
No test data available
No test data available
100 °C Literature
39 °C Closed Cup
No test data available
No
No test data available
No test data available
No test data available
1 Estimated.
0.98 at 20 °C Calculated.
Soluble
No data available
No test data available
Does not decompose.
No test data available
No data available
No test data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

# SECTION 10: STABILITY AND REACTIVITY

- **10.1 Reactivity:** No data available
- 10.2 Chemical stability: Stable.
- 10.3 Possibility of hazardous reactions: Polymerization will not occur.
- 10.4 Conditions to avoid: None known.

**10.5 Incompatible materials:** None known.

**10.6 Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials.

### SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

# 11.1 Information on toxicological effects Acute toxicity

#### Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. May cause central nervous system depression. May cause nausea and vomiting. Signs and symptoms of excessive exposure may include: Facial flushing. Low blood pressure. Irregular heartbeats. For the minor component(s): In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits.

Single dose oral LD50 has not been determined.

#### Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts. The dermal LD50 has not been determined.

#### Acute inhalation toxicity

With good ventilation, single exposure is not likely to be hazardous. In poorly ventilated areas, vapors or mists may accumulate and cause respiratory irritation. Prolonged excessive exposure may cause adverse effects. Excessive exposure (400 ppm) to isopropanol may cause eye, nose and throat irritation. Incoordination, confusion, hypotension, hypothermia, circulatory collapse, respiratory arrest and death may follow a longer duration or higher levels. Observations in animals include middle ear lining damage upon exposure to vapors of isopropanol. However, the relevance of this to humans is unknown For the minor component(s): In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits. The LC50 has not been determined.

#### Skin corrosion/irritation

Prolonged contact may cause skin irritation with local redness. May cause drying and flaking of the skin.

#### Serious eye damage/eye irritation

May cause pain disproportionate to the level of irritation to eye tissues. May cause moderate eye irritation. May cause moderate corneal injury. Vapor may cause eye irritation experienced as mild discomfort and redness. Vapor may cause lacrimation (tears).

#### Sensitization

For skin sensitization: For the component(s) tested: Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization: No relevant data found.

#### Specific Target Organ Systemic Toxicity (Single Exposure)

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3.

#### Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in animals: Kidney.

Liver.

Observations in animals include:

Lethargy.

Kidney effects and/or tumors have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans.

In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver.

Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits.

#### Carcinogenicity

In long-term animal studies with ethylene glycol butyl ether, small but statistically significant increases in tumors were observed in mice but not rats. The effects are not believed to be relevant to humans. If the material is handled in accordance with proper industrial handling procedures, exposures should not pose a carcinogenic risk to man.

#### Teratogenicity

Isopropanol has been toxic to the fetus in laboratory animals at doses toxic to the mother. Contains component(s) which did not cause birth defects in animals; other fetal effects occurred only at doses toxic to the mother.

#### **Reproductive toxicity**

In animal studies on component(s), effects on reproduction were seen only at doses that produced significant toxicity to the parent animals.

#### **Mutagenicity**

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

#### Aspiration Hazard

No aspiration toxicity classification

#### COMPONENTS INFLUENCING TOXICOLOGY:

#### **Isopropanol**

#### Acute oral toxicity

May cause central nervous system depression. Signs and symptoms of excessive exposure may include: Facial flushing. Low blood pressure. Irregular heartbeats. May cause nausea and vomiting.

LD50, Rat, 5,840 mg/kg OECD 401 or equivalent

#### Acute dermal toxicity

LD50, Rabbit, > 12,800 mg/kg

#### Acute inhalation toxicity

Observations in animals include middle ear lining damage upon exposure to vapors of isopropanol. However, the relevance of this to humans is unknown Excessive exposure (400 ppm) to isopropanol may cause eye, nose and throat irritation. Incoordination, confusion, hypotension, hypothermia, circulatory collapse, respiratory arrest and death may follow a longer duration or higher levels.

LC50, Rat, male and female, 6 Hour, vapour, > 10000 ppm

#### 2-butoxyethanol

#### Acute oral toxicity

In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits. LD50, Guinea pig, 1,400 mg/kg

LD50, Rat, 1,300 mg/kg

#### Acute dermal toxicity

Humans and guinea pigs are resistant to blood effects that are seen for rodents and rabbits. For this reason, the guinea pig data is used as the basis for the acute toxicity classification as it is a better model to assess acute toxicity to humans. LD50, Guinea pig, > 2,000 mg/kg

#### Acute inhalation toxicity

In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits. LCO, Guinea pig, 1 Hour, vapour, > 3.1 mg/l No deaths occurred at this concentration.

### **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicological information appears in this section when such data is available.

#### 12.1 Toxicity

#### **Isopropanol**

#### Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species). LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 9,640 mg/l, OECD Test Guideline 203 or Equivalent

#### Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), static test, 24 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent

#### Acute toxicity to algae/aquatic plants

NOEC, alga Scenedesmus sp., static test, 7 d, Growth inhibition (cell density reduction), 1,800 mg/l

ErC50, alga Scenedesmus sp., static test, 72 Hour, Growth rate inhibition, > 1,000 mg/l

#### Toxicity to bacteria

EC50, activated sludge, > 1,000 mg/l

#### Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, 30 mg/l

#### 2-butoxyethanol

#### Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 1,464 mg/l, OECD Test Guideline 203

#### Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 1,550 mg/l, OECD Test Guideline 202

#### Acute toxicity to algae/aquatic plants

EbC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Biomass, 911 mg/l, OECD Test Guideline 201

#### Toxicity to bacteria

IC50, Bacteria, Growth inhibition, > 1,000 mg/l

Chronic toxicity to fish

NOEC, Danio rerio (zebra fish), semi-static test, 21 d, > 100 mg/l

#### Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, Other, 100 mg/l

#### 12.2 Persistence and degradability

#### **Isopropanol**

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.
10-day Window: Pass
Biodegradation: 95 %
Exposure time: 21 d
Method: OECD Test Guideline 301E or Equivalent
10-day Window: Not applicable
Biodegradation: 53 %
Exposure time: 5 d
Method: Other guidelines

#### **Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	20 - 72 %

#### 2-butoxyethanol

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability). 10-day Window: Pass

**Biodegradation:** 90.4 % **Exposure time:** 28 d **Method:** OECD Test Guideline 301B or Equivalent

#### 12.3 Bioaccumulative potential

#### **Isopropanol**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3). **Partition coefficient: n-octanol/water(log Pow):** 0.05 Measured

#### 2-butoxyethanol

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3). **Partition coefficient:** n-octanol/water(log Pow): 0.81 Measured **Bioconcentration factor (BCF):** 3.2

#### 12.4 Mobility in soil

#### **Isopropanol**

Potential for mobility in soil is very high (Koc between 0 and 50). **Partition coefficient (Koc):** 1.1 Estimated.

#### 2-butoxyethanol

Potential for mobility in soil is high (Koc between 50 and 150). **Partition coefficient (Koc):** 67 Estimated.

#### 12.5 Results of PBT and vPvB assessment

#### **Isopropanol**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

#### 2-butoxyethanol

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

#### 12.6 Other adverse effects

#### **Isopropanol**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

#### 2-butoxyethanol

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

# SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Any disposal practice must be in compliance with all local and national laws and regulations. Do not dump into any sewers, on the ground, or into any body of water.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

**Treatment and disposal methods of used packaging:** Empty containers should be recycled or otherwise disposed of by an approved waste management facility. CONTAMINATED PACKAGING: Any disposal of contaminated packaging and washings must be in accordance with State, Territory and/or Local government regulations. After container has been cleaned and labelling has been removed, empty containers can be sent for recycling or disposal. If the container is to be reconditioned, the reconditioning company should be made aware of the nature of the original contents.

### SECTION 14: TRANSPORT INFORMATION

Classification for ROAD and Rail transport (ADR/RID): 14.1 UN number Not applicable

14.2	UN proper shipping name	Not regulated for transport
14.3	Transport hazard class(es)	Not applicable
14.4	Packing group	Not applicable
14.5	Environmental hazards	Not considered environmentally hazardous based on available data.
14.6	Special precautions for user	No data available.
Class	sification for SEA transport (IM	O-IMDG):
14.1	UN number	Not applicable
14.2	UN proper shipping name	Not regulated for transport
14.3	Transport hazard class(es)	Not applicable
14.4	Packing group	Not applicable
14.5	Environmental hazards	Not considered as marine pollutant based on available data.
14.6	Special precautions for user	No data available.
14.7	Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk
Class	sification for AIR transport (IAT	A/ICAO):
14.1	UN number	Not applicable
14.2	UN proper shipping name	Not regulated for transport
14.3	Transport hazard class(es)	Not applicable
14.4	Packing group	Not applicable

- **14.5** Environmental hazardsNot applicable
- **14.6** Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

# SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### REACh Regulation (EC) No 1907/2006

The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct., This product contains only components that have been either pre-registered, registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH).

# Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: FLAMMABLE LIQUIDS Number in Regulation: P5c 5,000 t 50,000 t

#### 15.2 Chemical safety assessment

Not applicable

# **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Eye Irrit. - 2 - H319 - Calculation method

#### Revision

Identification Number: 222069 / A279 / Issue Date: 05.01.2018 / Version: 15.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

#### Legend

2000/39/EC	Europe. Commission Directive 2000/39/EC establishing a first list of indicative	
	occupational exposure limit values	
ACGIH	USA. ACGIH Threshold Limit Values (TLV)	
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)	
GB EH40	UK. EH40 WEL - Workplace Exposure Limits	
GB EH40 BAT	UK. Biological monitoring guidance values	
SKIN	Absorbed via skin	

STEL	Short-term exposure limit
TWA	8-hour, time-weighted average
Acute Tox.	Acute toxicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure

#### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada): ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG -International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: TCSI - Taiwan Chemical Substance Inventory: TRGS -Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW CHEMICAL COMPANY LIMITED urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that

his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

GΒ