

# Technical Data Sheet

## SensorTack® release spray

### Description

SensorTack® release spray is used to separate SensorTack® from the refill mould.

### Use

Release spray to create SensorTack®2 silicone pads

### Characteristics

Very fine spray jet

Quick-drying

### Processing

Application: Shake well before use. Evenly spray the inner side of the refill mould from 10-20 cm distance to produce a thin film. Leave to dry for approx. 30 sec before applying mould to sensor.

### Container/Packaging

400 ml aerosol spray

### Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Without adequate ven-tilation, formation of explosive mixtures may be possible.

Storage stability: 12 months minimum

#### Disclaimer

Note:

The above information, in particular the suggestions for processing and use of our products, is based on our knowledge and experience in standard cases. To ensure that the above information in the technical data sheets can be complied with and the respective product used or processed properly, the products need to be stored correctly. In addition, the above information reflects our state of knowledge at the time of printing this note. We are constantly striving to improve our products, and as such reserve the right to make changes to product specifications and processing instructions. The most current technical data sheet at the time of processing/application shall apply. The user must therefore always check the suitability of the products for the intended application and obtain advance information of any changes to the product specifications at PMA/TOOLS. We would like to point out the following: In particular where our products are processed and used without observing the product specification and without complying with the current processing instructions, there will be no warranty for the processed or used product unless the customer (who processed the product) can prove that an alleged defect of the product was already present (i.e. independent of processing or use) when the risk passed from us to him as the customer. Due to the different materials, substrates and different working conditions when processing or using the product, no liability for any working results will be accepted in other regards, except where that we have provided an express assurance for a working result. We would like to point out that any such additional assurance would have to be presented and, if necessary, proved by the party relying on it, i.e. by the party asserting a warranty. In all other respects, our general terms and conditions apply.