



SAFETY DATA SHEET

DOW CHEMICAL COMPANY LIMITED

Safety Data Sheet according to Reg. (EU) No 2015/830

Product name: BETAPRIME™ 5504G

Revision Date: 16.02.2018

Version: 18.0

Date of last issue: 15.02.2017

Print Date: 17.02.2018

DOW CHEMICAL COMPANY LIMITED encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: BETAPRIME™ 5504G

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: A primer - For use in automotive applications.

1.3 Details of the supplier of the safety data sheet

COMPANY IDENTIFICATION

DOW CHEMICAL COMPANY LIMITED
STATION ROAD, BIRCH VALE, HIGH PEAK
DERBYSHIRE
England
SK22 1BR
UNITED KINGDOM

Customer Information Number:

+44 (0) 1663 746518

SDSQuestion@dow.com

Fax:

+44 (0) 1663 746605

1.4 EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 0031 115 694 982

Local Emergency Contact: 00 31 115 69 4982

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008:

Flammable liquids - Category 2 - H225

Eye irritation - Category 2 - H319

Respiratory sensitisation - Category 1 - H334

Skin sensitisation - Category 1 - H317

Specific target organ toxicity - single exposure - Category 3 - H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

Hazard pictograms



Signal word: DANGER

Hazard statements

H225	Highly flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P280	Wear protective gloves/ eye protection/ face protection.
P284	In case of inadequate ventilation wear respiratory protection.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Supplemental information

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

Contains Methyl ethyl ketone; Ethyl acetate; n-Butyl acetate; Phenol, 4-isocyanato-,1,1',1''-phosphorothionate, reaction products with 3-(trimethoxysilyl)-N-[3-(trimethoxysilyl)propyl]-1-propana; 4,4'-methylenediphenyl diisocyanate; 3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate

2.3 Other hazards

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

This product is a mixture.

CASRN / EC-No. / Index-No.	REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008
CASRN 78-93-3 EC-No. 201-159-0 Index-No. 606-002-00-3	01-2119457290-43	> 35.0 - < 45.0 %	Methyl ethyl ketone	Flam. Liq. - 2 - H225 Eye Irrit. - 2 - H319 STOT SE - 3 - H336
CASRN 141-78-6 EC-No. 205-500-4 Index-No. 607-022-00-5	01-2119475103-46	> 10.0 - < 15.0 %	Ethyl acetate	Flam. Liq. - 2 - H225 Eye Irrit. - 2 - H319 STOT SE - 3 - H336
CASRN 4435-53-4 EC-No. 224-644-9 Index-No. -	-	< 10.0 %	3-Methoxy-1-butyl acetate	Not classified
CASRN 4151-51-3 EC-No. 223-981-9 Index-No. -	01-2119948848-16	< 10.0 %	Phenol, 4-isocyanato-, phosphorothioate (3:1) (ester)	Acute Tox. - 4 - H302
CASRN 108-65-6 EC-No. 203-603-9 Index-No. 607-195-00-7	01-2119475791-29	< 10.0 %	2-methoxy-1-methylethyl acetate	Flam. Liq. - 3 - H226 STOT SE - 3 - H336
CASRN 950747-06-5 EC-No. 480-190-3 Index-No. -	01-0000020067-76	> 1.0 - < 5.0 %	Phenol, 4-isocyanato-,1,1',1''-phosphorothionate, reaction products with 3-(trimethoxysilyl)-N-[3-(trimethoxysilyl)propyl]-1-propana	Resp. Sens. - 1 - H334 Skin Sens. - 1 - H317 Aquatic Chronic - 4 - H413

CASRN 123-86-4 EC-No. 204-658-1 Index-No. 607-025-00-1	01-2119485493-29	> 1.0 - < 5.0 %	n-Butyl acetate	Flam. Liq. - 3 - H226 STOT SE - 3 - H336
CASRN 4098-71-9 EC-No. 223-861-6 Index-No. 615-008-00-5	01-2119490408-31	< 0.5 %	3- Isocyanatomethyl- 3,5,5- trimethylcyclohexyl isocyanate; isophorone di- isocyanate	Acute Tox. - 1 - H330 Skin Irrit. - 2 - H315 Eye Irrit. - 2 - H319 Resp. Sens. - 1 - H334 Skin Sens. - 1 - H317 STOT SE - 3 - H335 Aquatic Chronic - 2 - H411
CASRN 108-90-7 EC-No. 203-628-5 Index-No. 602-033-00-1	—	< 0.5 %	Chlorobenzene	Flam. Liq. - 3 - H226 Acute Tox. - 4 - H332 Skin Irrit. - 2 - H315 Aquatic Chronic - 2 - H411
CASRN 101-68-8 EC-No. 202-966-0 Index-No. 615-005-00-9	01-2119457014-47	> 0.1 - < 1.0 %	4,4'- methylenediphenyl diisocyanate	Acute Tox. - 4 - H332 Skin Irrit. - 2 - H315 Eye Irrit. - 2 - H319 Resp. Sens. - 1 - H334 Skin Sens. - 1 - H317 Carc. - 2 - H351 STOT SE - 3 - H335 STOT RE - 2 - H373

If present in this product, any not classified components disclosed above for which no country specific OEL value(s) is(are) indicated under Section 8, are being disclosed as voluntarily disclosed components.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. An MDI skin decontamination study demonstrated that cleaning very soon after exposure is important, and that a polyglycol-based skin cleanser or corn oil may be more effective than soap and water. This may also apply to other isocyanates. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.

Eye contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

4.2 Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. May cause respiratory sensitization or asthma-like symptoms. Bronchodilators, expectorants and antitussives may be of help. Treat bronchospasm with inhaled beta2 agonist and oral or parenteral corticosteroids. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. If you are sensitized to diisocyanates, consult your physician regarding working with other respiratory irritants or sensitizers. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. Straight or direct water streams may not be effective to extinguish fire.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may vent and/or rupture due to fire. Electrically ground and bond all equipment. Flammable mixtures of this product are readily ignited even by static discharge. Vapors are heavier than air and may travel a long distance and accumulate in low lying

areas. Ignition and/or flash back may occur. Flammable mixtures may exist within the vapor space of containers at room temperature. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.

5.3 Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water may not be effective in extinguishing fire. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Avoid accumulation of water. Product may be carried across water surface spreading fire or contacting an ignition source. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Evacuate area. Only trained and properly protected personnel must be involved in clean-up operations. Keep personnel out of low areas. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. For large spills, warn public of downwind explosion hazard. Check area with combustible gas detector before reentering area. Ground and bond all containers and handling equipment. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

6.2 Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

6.3 Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Cat litter. Sand. Sawdust. Ground and bond all containers and handling equipment. Pump with explosion-proof equipment. If available, use foam to smother or suppress. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

6.4 Reference to other sections: References to other sections, if applicable, have been provided in the previous sub-sections.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: Keep away from heat, sparks and flame. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Do not swallow. Avoid breathing vapor. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation. No smoking, open flames or sources of ignition in handling and storage area. Ignition sources can include and are not limited to pilot lights, flames, smoking, sparks, heaters, electrical equipment, and static discharges. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Never use air pressure for transferring product unless a risk assessment has been conducted that includes consideration of the flammability of the product. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

7.2 Conditions for safe storage, including any incompatibilities: Minimize sources of ignition, such as static build-up, heat, spark or flame. Keep container closed. Flammable mixtures may exist within the vapor space of containers at room temperature. Store in a dry place. Avoid moisture.

Storage stability

Storage temperature:

> 5 - < 25 °C

7.3 Specific end use(s): See the technical data sheet on this product for further information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Methyl ethyl ketone	ACGIH	TWA	200 ppm
	ACGIH	STEL	300 ppm
	Dow IHG	TWA	50 ppm
	Dow IHG	STEL	100 ppm
	2000/39/EC	TWA	600 mg/m ³ 200 ppm
	2000/39/EC	STEL	900 mg/m ³ 300 ppm
	GB EH40	TWA	SKIN
	GB EH40	STEL	SKIN
	GB EH40	TWA	600 mg/m ³ 200 ppm
	GB EH40	STEL	899 mg/m ³ 300 ppm
Ethyl acetate	ACGIH	TWA	400 ppm
	Dow IHG	TWA	150 ppm
	Dow IHG	STEL	300 ppm
	GB EH40	TWA	200 ppm
	GB EH40	STEL	400 ppm
	2017/164/EU	STEL	1,468 mg/m ³ 400 ppm

Phenol, 4-isocyanato-, phosphorothioate (3:1) (ester)	2017/164/EU	TWA	734 mg/m3 200 ppm	
	GB EH40	TWA	0.02 mg/m3 , NCO	
2-methoxy-1-methylethyl acetate	GB EH40	STEL	0.07 mg/m3 , NCO	
	US WEEL	TWA	50 ppm	
n-Butyl acetate	Dow IHG	TWA	30 ppm	
	Dow IHG	TWA	SKIN	
	Dow IHG	STEL	90 ppm	
	Dow IHG	STEL	SKIN	
	2000/39/EC	STEL	550 mg/m3 100 ppm	
	2000/39/EC	TWA	SKIN	
	2000/39/EC	TWA	275 mg/m3 50 ppm	
	2000/39/EC	STEL	SKIN	
	GB EH40	TWA	SKIN	
	GB EH40	STEL	SKIN	
	GB EH40	TWA	274 mg/m3 50 ppm	
	GB EH40	STEL	548 mg/m3 100 ppm	
	ACGIH	TWA	50 ppm	
	ACGIH	STEL	150 ppm	
	Dow IHG	TWA	75 ppm	
Dow IHG	STEL	150 ppm		
3-Isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate; isophorone di- isocyanate	GB EH40	TWA	724 mg/m3 150 ppm	
	GB EH40	STEL	966 mg/m3 200 ppm	
	ACGIH	TWA	0.005 ppm	
Chlorobenzene	Dow IHG	TWA	0.005 ppm	
	Dow IHG	TWA	Skin and respiratory sensitiser	
	GB EH40	TWA	SEN	
	GB EH40	STEL	SEN	
	GB EH40	TWA	0.02 mg/m3 , NCO	
	GB EH40	STEL	0.07 mg/m3 , NCO	
	ACGIH	TWA	10 ppm	
	2006/15/EC	TWA	23 mg/m3 5 ppm	
	2006/15/EC	STEL	70 mg/m3 15 ppm	
	GB EH40	TWA	SKIN	
	GB EH40	STEL	SKIN	
	GB EH40	TWA	1 ppm	
	GB EH40	STEL	3 ppm	
	4,4'-methylenediphenyl diisocyanate	ACGIH	TWA	0.005 ppm
		Dow IHG	TWA	0.005 ppm
Dow IHG		STEL	0.02 ppm	
	GB EH40	TWA	SEN	

GB EH40	STEL	SEN
GB EH40	TWA	0.02 mg/m ³ , NCO
GB EH40	STEL	0.07 mg/m ³ , NCO

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methyl ethyl ketone	78-93-3	butan-2-one	Urine	After shift	70 micromol per litre	GB EH40 BAT
		methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Phenol, 4-isocyanato-, phosphorothioate (3:1) (ester)	4151-51-3	urinary diamine (Isocyanate s)	Urine	Post task	1 µmol/mol creatinine	GB EH40 BAT
2-methoxy-1-methylethyl acetate	108-65-6				100 mg/g	
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate	4098-71-9	urinary diamine (Isocyanate s)	Urine	Post task	1 µmol/mol creatinine	GB EH40 BAT
Chlorobenzene	108-90-7	4-Chlorocatechol	Urine	End of shift at end of workweek	100 mg/g Creatinine	ACGIH BEI
		p-Chlorophenol	Urine	End of shift at end of workweek	20 mg/g Creatinine	ACGIH BEI
4,4'-methylenediphenyl diisocyanate	101-68-8	urinary diamine (Isocyanate s)	Urine	Post task	1 µmol/mol creatinine	GB EH40 BAT

Derived No Effect Level

Methyl ethyl ketone

Workers

Acute systemic effects		Acute local effects		Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation

n.a.	n.a.	n.a.	n.a.	1161 mg/kg bw/day 41 2 mg/kg bw/day	600 mg/m3	n.a.	n.a.
------	------	------	------	--	-----------	------	------

Consumers

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	106 mg/m3	31 mg/kg bw/day	n.a.	n.a.

2-methoxy-1-methylethyl acetate

Workers

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	550 mg/m3	796 mg/kg bw/day	275 mg/m3	n.a.	n.a.

Consumers

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	320 mg/kg bw/day	33 mg/m3	36 mg/kg bw/day	n.a.	33 mg/m3

n-Butyl acetate

Workers

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	600 mg/m3	11 mg/kg bw/day	600 mg/m3	11 mg/kg bw/day	300 mg/m3	n.a.	300 mg/m3

Consumers

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
6 mg/kg bw/day	300 mg/m3	2 mg/kg bw/day	n.a.	300 mg/m3	6 mg/kg bw/day	35.7 mg/m3	2 mg/kg bw/day	n.a.	35.7 mg/m3

Chlorobenzene

Workers

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation

15 mg/kg bw/day	70 mg/m ³	n.a.	n.a.	5 mg/kg bw/day	23 mg/m ³	n.a.	n.a.
--------------------	----------------------	------	------	-------------------	----------------------	------	------

Consumers

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
3 mg/kg bw/day	1 mg/m ³	3 mg/kg bw/day	n.a.	n.a.	3 mg/kg bw/day	1 mg/m ³	3 mg/kg bw/day	n.a.	n.a.

4,4'-methylenediphenyl diisocyanate

Workers

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	0.1 mg/m ³	n.a.	n.a.	n.a.	0.05 mg/m ³

Consumers

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	0.05 mg/m ³	n.a.	n.a.	n.a.	n.a.	0.025 mg/m ³

Predicted No Effect Concentration

Methyl ethyl ketone

Compartment	PNEC
Fresh water	55.8 mg/l
Marine water	55.8 mg/l
Intermittent use/release	55.8 mg/l
Sewage treatment plant	709 mg/l
Fresh water sediment	284.74 mg/kg
Marine sediment	284.7 mg/kg
Soil	22.5 mg/kg
Oral (Secondary Poisoning)	1000 mg/kg food

2-methoxy-1-methylethyl acetate

Compartment	PNEC
Fresh water	0.635 mg/l
Marine water	0.0635 mg/l
Intermittent use/release	6.35 mg/l
Sewage treatment plant	100 mg/l
Fresh water sediment	3.29 mg/kg dry weight (d.w.)
Marine sediment	0.329 mg/kg dry weight (d.w.)
Soil	0.29 mg/kg dry weight (d.w.)

n-Butyl acetate

Compartment	PNEC
Fresh water	0.18 mg/l
Marine water	0.018 mg/l
Intermittent use/release	0.36 mg/l
Fresh water sediment	0.981 mg/kg dry weight (d.w.)
Marine sediment	0.0981 mg/kg dry weight (d.w.)
Soil	0.09 mg/kg dry weight (d.w.)
Sewage treatment plant	35.6 mg/l

Chlorobenzene

Compartment	PNEC
Fresh water	0.032 mg/l
Marine water	0.003 mg/l
Sewage treatment plant	1.4 mg/l
Fresh water sediment	0.922 mg/kg dry weight (d.w.)
Marine sediment	0.092 mg/kg dry weight (d.w.)
Soil	0.166 mg/kg dry weight (d.w.)
Oral (Secondary Poisoning)	10 mg/kg food

4,4'-methylenediphenyl diisocyanate

Compartment	PNEC
Fresh water	1 mg/l
Marine water	0.1 mg/l
Intermittent use/release	10 mg/l
Soil	1 mg/kg dry weight (d.w.)
Sewage treatment plant	1 mg/l

8.2 Exposure controls

Engineering controls: Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. The odor and irritancy of this material are inadequate to warn of excessive exposure.

Individual protection measures

Eye/face protection: Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent. If exposure causes eye discomfort, use a full-face respirator.

Skin protection

Hand protection: Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Polyethylene. Ethyl vinyl alcohol

laminate ("EVAL"). Examples of acceptable glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Viton. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Atmospheric levels should be maintained below the exposure guideline. When atmospheric levels may exceed the exposure guideline, use an approved air-purifying respirator equipped with an organic vapor sorbent and a particle filter. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure air-supplying respirator (air line or self-contained breathing apparatus). For emergency response or for situations where the atmospheric level is unknown, use an approved positive-pressure self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a highly toxic particulate pre-filter, type AP3.

Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Color	Black
Odor	Solvent
Odor Threshold	No test data available
pH	No test data available

Melting point/range	No test data available
Freezing point	No test data available
Boiling point (760 mmHg)	80 °C <i>Literature</i>
Flash point	closed cup -10.00 °C <i>Estimated.</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Flammable liquid
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	No test data available
Relative Vapor Density (air = 1)	No test data available
Relative Density (water = 1)	0.9527 <i>Calculated.</i>
Water solubility	No test data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No test data available
Decomposition temperature	No test data available
Dynamic Viscosity	No test data available
Kinematic Viscosity	No test data available
Explosive properties	No test data available
Oxidizing properties	No test data available

9.2 Other information

Molecular weight No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: No dangerous reaction known under conditions of normal use.

10.2 Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.

10.3 Possibility of hazardous reactions: Polymerization will not occur.

10.4 Conditions to avoid: Exposure to elevated temperatures can cause product to decompose. Avoid static discharge.

10.5 Incompatible materials: Avoid contact with: Acids. Bases. Oxidizers.

10.6 Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. May cause central nervous system effects.

Single dose oral LD50 has not been determined.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

The dermal LD50 has not been determined.

Acute inhalation toxicity

Vapor concentrations are attainable which could be hazardous on single exposure. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. May cause nausea and vomiting. For the minor component(s): Methylene diphenyl diisocyanate (MDI). Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause pulmonary edema (fluid in the lungs.) Effects may be delayed. Decreased lung function has been associated with overexposure to isocyanates. This material contains mineral and/or inorganic fillers. There is essentially no potential for inhalation exposure to these fillers incidental to industrial handling due to the physical state. As product: The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.

Prolonged contact may cause moderate skin irritation with local redness.

May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause pain disproportionate to the level of irritation to eye tissues.

May cause moderate eye irritation which may be slow to heal.

May cause moderate corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Sensitization

For skin sensitization:

A component in this mixture has been shown to be a skin sensitizer.

Once an individual is sensitized, reexposure to very small amounts of vapor, mist or liquid isophorone diisocyanate may cause an allergic skin reaction.

Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.

For respiratory sensitization:

A component in this mixture may cause an allergic respiratory response.

Reexposure to extremely low isocyanate concentrations may cause allergic respiratory reactions in individuals already sensitized.

Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest.

Occasionally, breathing difficulties may be life threatening.

Specific Target Organ Systemic Toxicity (Single Exposure)

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in animals: Liver.

Respiratory tract.

Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

Methyl ethyl ketone has caused liver effects in laboratory animals exposed by inhalation to high concentrations.

Methyl ethyl ketone is probably not neurotoxic in itself but it potentiates the neurotoxicity of methyl-n-butyl ketone and n-hexane.

Carcinogenicity

Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m³) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI. Contains component(s) which have caused cancer in some laboratory animals.

Teratogenicity

Contains component(s) which did not cause birth defects in animals; other fetal effects occurred only at doses toxic to the mother. Contains component(s) which caused birth defects in laboratory animals only at doses toxic to the mother.

Reproductive toxicity

For the component(s) tested: In animal studies, did not interfere with reproduction.

Mutagenicity

For the component(s) tested: In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

No aspiration toxicity classification

COMPONENTS INFLUENCING TOXICOLOGY:

Methyl ethyl ketone

Acute oral toxicity

LD50, Rat, 2,657 - 5,554 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 5,000 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, 34.5 mg/l

Ethyl acetate

Acute oral toxicity

LD50, Rabbit, 4,934 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 17,900 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, > 28.6 mg/l

3-Methoxy-1-butyl acetate

Acute oral toxicity

LD50, Rat, 4,210 mg/kg

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

Phenol, 4-isocyanato-, phosphorothioate (3:1) (ester)

Acute oral toxicity

LC50, Rat, male and female, > 675 mg/kg Estimated.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

Rat, male, 4 Hour, dust/mist, 5.7 mg/l

Rat, female, 4 Hour, dust/mist, > 6.6 mg/l

2-methoxy-1-methylethyl acetate

Acute oral toxicity

Observations in animals include: Lethargy. LD50, Rat, > 5,000 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 5,000 mg/kg

Acute inhalation toxicity

LC0, Rat, 6 Hour, vapour, > 23.5 mg/l No deaths occurred at this concentration.

Phenol, 4-isocyanato-, 1,1',1''-phosphorothionate, reaction products with 3-(trimethoxysilyl)-N-[3-(trimethoxysilyl)propyl]-1-propana

Acute oral toxicity

LD50, Rat, female, > 2,000 mg/kg No deaths occurred at this concentration.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

n-Butyl acetate

Acute oral toxicity

LD50, Rat, male, 12,789 mg/kg

LD50 Oral, Rat, female, 10,760 mg/kg

Acute dermal toxicity

LD50, Rabbit, male and female, > 14,112 mg/kg

Acute inhalation toxicity

The LC50 has not been determined.

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate

Acute oral toxicity

LD50, Rat, 4,825 mg/kg

Acute dermal toxicity

LD50, Rat, > 7,000 mg/kg

Acute inhalation toxicity

LC50, Rat, male and female, 4 Hour, dust/mist, 0.04 mg/l

Chlorobenzene

Acute oral toxicity

LD50, Rat, male and female, > 2,000 mg/kg OECD Test Guideline 401

Acute dermal toxicity

LD50, Rabbit, > 2,212 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, 29.7 mg/l OECD Test Guideline 403

4,4'-methylenediphenyl diisocyanate

Acute oral toxicity

LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.

Acute dermal toxicity

LD50, Rabbit, > 9,400 mg/kg

Acute inhalation toxicity

LC50, Rat, 1 Hour, dust/mist, 2.24 mg/l

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

12.1 Toxicity

Methyl ethyl ketone

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, 2,993 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 308 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (microalgae), static test, 96 Hour, Growth rate inhibition, 2,029 mg/l, OECD Test Guideline 201

Ethyl acetate

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Pimephales promelas (fathead minnow), 96 Hour, 230 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, 3,090 mg/l, DIN 38412

Acute toxicity to algae/aquatic plants

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline 201

Chronic toxicity to fish

NOEC, Pimephales promelas (fathead minnow), 32 d, < 9.65 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 2.4 mg/l

3-Methoxy-1-butyl acetate

Acute toxicity to fish

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

LC50, Danio rerio (zebra fish), semi-static test, 96 Hour, 7.1 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, 360 mg/l

LC50, crustacean Chaetogammarus marinus, 96 Hour, 128 mg/l

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, > 70 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, Bacteria, 16 Hour, > 1,000 mg/l

Phenol, 4-isocyanato-, phosphorothioate (3:1) (ester)**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
Material is not classified as dangerous to aquatic organisms (10 < LC50/EC50/IC50/LL50/EL50 <= 100 mg/L and NOEC > 1mg/l in the most sensitive species).
LC50, Danio rerio (zebra fish), 96 Hour, > 100 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

Acute toxicity to algae/aquatic plants

ErC50, Algae (Scenedesmus subspicatus), 72 Hour, Growth rate, > 100 mg/l
NOEC, Algae (Scenedesmus subspicatus), 72 Hour, Growth rate, > 100 mg/l

Toxicity to bacteria

EC50, activated sludge, 3 Hour, Respiration rates., > 1,000 mg/l

2-methoxy-1-methylethyl acetate**Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).
LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 134 mg/l, Method Not Specified.

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 408 mg/l, Method Not Specified.

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (microalgae), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 201 or Equivalent

Phenol, 4-isocyanato-, 1,1',1''-phosphorothionate, reaction products with 3-(trimethoxysilyl)-N-[3-(trimethoxysilyl)propyl]-1-propana**Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

EL50, Desmodesmus subspicatus (green algae), Growth inhibition, 72 Hour, Growth rate inhibition, > 160 mg/l, OECD Test Guideline 201 or Equivalent

n-Butyl acetate

Acute toxicity to fish

Material is harmful to aquatic organisms (LC50/EC50/IC50 between 10 and 100 mg/L in the most sensitive species).

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 18 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, 44 mg/l, Method Not Specified.

Acute toxicity to algae/aquatic plants

ErC50, Desmodesmus subspicatus (green algae), 72 Hour, Growth rate inhibition, 648 mg/l

Toxicity to bacteria

EC50, Bacteria, 16 Hour, > 1,000 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, 23 mg/l

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate

Acute toxicity to fish

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

For this family of materials:

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species.

LC50, Leuciscus idus (Golden orfe), static test, 48 Hour, 1.8 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 24 Hour, 84 mg/l

Acute toxicity to algae/aquatic plants

EbC50, alga Scenedesmus sp., 72 Hour, Biomass, 119 mg/l

Toxicity to bacteria

EC10, Bacteria, 6 Hour, 554 mg/l

Chlorobenzene

Acute toxicity to fish

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

LC50, Lepomis macrochirus (Bluegill sunfish), 96 Hour, 4.5 mg/l, OECD Test Guideline 203 or Equivalent

LC50, Oncorhynchus mykiss (rainbow trout), flow-through test, 96 Hour, 7.5 mg/l, Method Not Specified.

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), Static, 48 Hour, 26 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate, 11.4 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, 30 min, 140 mg/l, OECD Test Guideline 209

Chronic toxicity to fish

NOEC, Danio rerio (zebra fish), 28 d, 4.8 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, 0.32 mg/l

Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 2 d, survival, 29 mg/cm²

4,4'-methylenediphenyl diisocyanate**Acute toxicity to fish**

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species.

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Based on information for a similar material:

LC50, Danio rerio (zebra fish), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

Based on information for a similar material:

EC50, Daphnia magna (Water flea), static test, 24 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

Based on information for a similar material:

NOEC, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, 1,640 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

Based on information for a similar material:

EC50, activated sludge, static test, 3 Hour, Respiration rates., > 100 mg/l

Toxicity to soil-dwelling organisms

EC50, Eisenia fetida (earthworms), Based on information for a similar material:, 14 d, > 1,000 mg/kg

Toxicity to terrestrial plants

EC50, Avena sativa (oats), Growth inhibition, 1,000 mg/l

EC50, Lactuca sativa (lettuce), Growth inhibition, 1,000 mg/l

12.2 Persistence and degradability

Methyl ethyl ketone

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 98 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Ethyl acetate

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 100 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

3-Methoxy-1-butyl acetate

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Pass

Biodegradation: > 90 %

Exposure time: 12 d

Method: OECD Test Guideline 301E or Equivalent

10-day Window: Not applicable

Biodegradation: > 95 %

Exposure time: 20 d

Method: OECD Test Guideline 302B or Equivalent

10-day Window: Not applicable

Biodegradation: 63.5 %

Exposure time: 14 d

Method: OECD Test Guideline 301C or Equivalent

Theoretical Oxygen Demand: 1.97 mg/mg

Photodegradation

Atmospheric half-life: 0.57 d

Method: Estimated.

Phenol, 4-isocyanato-, phosphorothioate (3:1) (ester)

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 58.2 %

Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 0.165 d

Method: Estimated.

2-methoxy-1-methylethyl acetate

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Pass

Biodegradation: 83 %

Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

10-day Window: Not applicable

Biodegradation: 100 %

Exposure time: 28 d

Method: OECD Test Guideline 302B or Equivalent

Phenol, 4-isocyanato-,1,1',1"-phosphorothionate, reaction products with 3-(trimethoxysilyl)-N-[3-(trimethoxysilyl)propyl]-1-propana

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 23 %

Exposure time: 28 d

Method: OECD Test Guideline 301B or Equivalent

n-Butyl acetate

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 83 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions. For this family of materials: In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

10-day Window: Fail

Biodegradation: 62 %

Exposure time: 28 d

Method: OECD Test Guideline 301E or Equivalent

Chlorobenzene

Biodegradability: Biodegradation under aerobic static laboratory conditions is high (BOD20 or BOD28/ThOD > 40%).

10-day Window: Not applicable

Biodegradation: 15 %
Exposure time: 28 d
Method: OECD Test Guideline 301C or Equivalent

Theoretical Oxygen Demand: 1.99 mg/mg

4,4'-methylenediphenyl diisocyanate

Biodegradability: In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

10-day Window: Not applicable

Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 302C or Equivalent

12.3 Bioaccumulative potential

Methyl ethyl ketone

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.29 Measured

Ethyl acetate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.68 Measured

Bioconcentration factor (BCF): 30 Fish Measured

3-Methoxy-1-butyl acetate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1.01 Estimated.

Phenol, 4-isocyanato-, phosphorothioate (3:1) (ester)

Bioaccumulation: Bioconcentration potential is low (BCF less than 100 or log Pow greater than 7).

Partition coefficient: n-octanol/water(log Pow): 8.27 Estimated.

2-methoxy-1-methylethyl acetate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1.2 Measured

Phenol, 4-isocyanato-, 1,1',1''-phosphorothionate, reaction products with 3-(trimethoxysilyl)-N-[3-(trimethoxysilyl)propyl]-1-propana

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient: n-octanol/water(log Pow): > 6.5 Estimated.

n-Butyl acetate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): Pow: 3.2 at 25 °C Measured

Bioconcentration factor (BCF): 15 Fish Estimated.

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate

Bioaccumulation: For this family of materials: In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Partition coefficient: n-octanol/water(log Pow): 4.75 Estimated.

Chlorobenzene

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 2.89 Measured

Bioconcentration factor (BCF): 3.9 - 40 Cyprinus carpio (Carp) OECD Test Guideline 305 or Equivalent

4,4'-methylenediphenyl diisocyanate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). Reacts with water. In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Bioconcentration factor (BCF): 92 Cyprinus carpio (Carp) 28 d

12.4 Mobility in soil**Methyl ethyl ketone**

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 3.8 Estimated.

Ethyl acetate

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 3 Estimated.

3-Methoxy-1-butyl acetate

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 10 Estimated.

Phenol, 4-isocyanato-, phosphorothioate (3:1) (ester)

Expected to be relatively immobile in soil (Koc > 5000).

Partition coefficient (Koc): > 5000 Estimated.

2-methoxy-1-methylethyl acetate

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 1.7 Estimated.

Phenol, 4-isocyanato-, 1,1',1"-phosphorothionate, reaction products with 3-(trimethoxysilyl)-N-[3-(trimethoxysilyl)propyl]-1-propana

No data available.

n-Butyl acetate

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 19 - 70 Estimated.

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate

For this family of materials:

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Partition coefficient (Koc): 36000 Estimated.

Chlorobenzene

Potential for mobility in soil is high (Koc between 50 and 150).

Partition coefficient (Koc): 79 Measured

4,4'-methylenediphenyl diisocyanate

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

12.5 Results of PBT and vPvB assessment

Methyl ethyl ketone

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Ethyl acetate

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Phenol, 4-isocyanato-, phosphorothioate (3:1) (ester)

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

2-methoxy-1-methylethyl acetate

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Phenol, 4-isocyanato-,1,1',1"-phosphorothionate, reaction products with 3-(trimethoxysilyl)-N-[3-(trimethoxysilyl)propyl]-1-propana

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

n-Butyl acetate

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Chlorobenzene

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

4,4'-methylenediphenyl diisocyanate

This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

12.6 Other adverse effects

Methyl ethyl ketone

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Ethyl acetate

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

3-Methoxy-1-butyl acetate

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Phenol, 4-isocyanato-, phosphorothioate (3:1) (ester)

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

2-methoxy-1-methylethyl acetate

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Phenol, 4-isocyanato-, 1,1',1''-phosphorothionate, reaction products with 3-(trimethoxysilyl)-N-[3-(trimethoxysilyl)propyl]-1-propana

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

n-Butyl acetate

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Chlorobenzene

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

4,4'-methylenediphenyl diisocyanate

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required. Do not dump into any sewers, on the ground, or into any body of water. Incineration under approved, controlled conditions using incinerators suitable or designed for the disposal of hazardous chemical wastes, is the preferred method for disposal.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. **CONTAMINATED PACKAGING:** Any disposal of contaminated packaging and washings must be in accordance with State, Territory and/or Local government regulations. After container has been cleaned and labelling has been removed, empty containers can be sent for recycling or disposal. If the container is to be reconditioned, the reconditioning company should be made aware of the nature of the original contents.

SECTION 14: TRANSPORT INFORMATION

Classification for ROAD and Rail transport (ADR/RID):

14.1 UN number	UN 1139
14.2 UN proper shipping name	COATING SOLUTION
14.3 Transport hazard class(es)	3
14.4 Packing group	II
14.5 Environmental hazards	Not considered environmentally hazardous based on available data.
14.6 Special precautions for user	Special Provision 640D Hazard Identification Number: 33

Classification for SEA transport (IMO-IMDG):

14.1 UN number	UN 1139
14.2 UN proper shipping name	COATING SOLUTION
14.3 Transport hazard class(es)	3
14.4 Packing group	II
14.5 Environmental hazards	Not considered as marine pollutant based on available data.
14.6 Special precautions for user	EmS: F-E, S-E
14.7 Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

14.1 UN number	UN 1139
14.2 UN proper shipping name	Coating solution
14.3 Transport hazard class(es)	3
14.4 Packing group	II
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation (EC) No 1907/2006

This product contains only components that have been either pre-registered, are exempt from registration or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH). The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

Restrictions on the manufacture, placing on the market and use:

The following substance/s contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product have to comply with the restrictions placed upon it by the aforementioned provision.

CAS-No.: 101-68-8	Name: 4,4'-methylenediphenyl diisocyanate
-------------------	---

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: FLAMMABLE LIQUIDS

Number in Regulation: P5c

5,000 t

50,000 t

15.2 Chemical safety assessment

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.

H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Flam. Liq. - 2 - H225 - On basis of test data.

Eye Irrit. - 2 - H319 - Calculation method

Resp. Sens. - 1 - H334 - Calculation method

Skin Sens. - 1 - H317 - Calculation method

STOT SE - 3 - H336 - Calculation method

Revision

Identification Number: 361268 / A279 / Issue Date: 16.02.2018 / Version: 18.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

2000/39/EC	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	Europe. Indicative occupational exposure limit values
2017/164/EU	Commission Directive (EU) 2017/164 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
Dow IHG	Dow Industrial Hygiene Guideline
GB EH40	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	UK. Biological monitoring guidance values
SEN	Sensitizer
SKIN	Absorbed via skin
STEL	Short Term Exposure Limit (STEL):
TWA	Time Weighted Average (TWA):
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)
Acute Tox.	Acute toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Resp. Sens.	Respiratory sensitisation
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW CHEMICAL COMPANY LIMITED urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

GB

